

LORAD 2.5 CS-EU MAINS CORD SET

Screened Mains Cord Set, 250V/10A


Gauge: 3x2.5mm² / AWG 13

Rev.date: 2022-08-30

Customs tariff no: 8544499500

Country of origin: Sweden

- Screened mains flex cable
- Gold plated Connectors
- Tin plated OFC wires - Corrosion resistant
- Protects both from electric & magnetic fields.



LoRad - Low Radiation

Shielded cord set comprising Supra LoRad 3 x 2.5 mm² cable, Supra SWF10 female connector (IEC-320) and Supra SW-EU male plug. Current rating 10 A continuously. EU-version, with straight Schuko plug, is the most common standard throughout Europe. Exceptions are Denmark, Italy, Switzerland, Ireland and Britain. Fits our LoRad mains power distribution blocks rated 10A. LoRad means Low Radiation and the design of these mains flex cables minimises both electric and magnetic alternating fields. Allow your hi-fi gear the most welcome benefit of all, the possibility to be silent, when supposed to. Only then, the tiniest details and notes will become clearly audible. LoRad protects both from alternating fields radiating from the cable as well as from pick-up of surrounding airborne noise fields.

- Short pitch twisting of the lead cores cancels the magnetic alternating fields and will not infect adjacent interconnects with noise feedback.
- LoRad will result in a cleaner sound, better picture and a more healthy home and working environment with low levels of harmful fields.
- The screen protects your equipment from radiated mains, RF pick-up.

CONSTRUCTION

Cable: [LoRad 3x2.5](#)
 Cross section area: 3x2.5mm² / AWG 13
 Screen: Semi-conductive Nylon tape, black, 100%
 Jacket: PVC GA78, round
 Diameter: 11mm
 Cable colour: Iceblue (other colours upon order)
 Marking: SUPRA LORAD 3G2.5 + Made in Sweden + Meter mark
 Connectors: SW-EU Schuko male to SWF-10s 10A C13 IEC320 female plug
 - Pin Material: 24K Gold plated Copper
 - Pin connection: Screw/clamp
 - Colour: Anthracite Grey
 Cable direction: Follow the arrows > Wall socket > Power inlet
 Rated Voltage/current: 250V / 10A
 Packing: 1-2m Blister 25x21.5x4.8cm, 4m Blister 31,5x25,4x6,0cm



Note! The connector must be connected to a wall socket with a ground terminal for the full LoRad effect to take place. LoRad are tested and certified by Intertek Sweden, meeting the European safety regulation HD21.5 S3.

Standard lengths as below, special length cables upon order.

PRODUCT	Qty	Part.no	EAN-13	E-no	Crt	Weight
LORAD 2.5 CS-EU 1M	1PC	3004100263	7330060200045	2403787	25	0,37
LORAD 2.5 CS-EU 1.5M	1PC	3004100099	7330060009082	2403788	25	0,48
LORAD 2.5 CS-EU 2M	1PC	3004100081	7330060009099	2403789	25	0,58
LORAD 2.5 CS-EU 4M	1PC	3004100271	7330060200052	2403790	13	1,04

