



A Legend Reborn

The 805 Diamond is an industry world-first for a speaker of this size and price point - the only one of its kind to incorporate the true studio grade technology of the diamond dome tweeter. Experience remarkable, lifelike sound from a discreet speaker that fits almost anywhere.

Technical Specifications

Technical features Free-mounted diamond dome tweeter

Nautilus™ tube tweeter loading Quad magnet tweeter motor

Kevlar® brand fibre cone bass/midrange Matrix™ cabinet

Flowport™

Description 2-way vented-box system

Drive units 1x ø25mm (1 in) diamond dome high-frequency

1x ø165mm (6.5 in) woven Kevlar® cone bass/midrange

Frequency range -6dB at 42Hz and 33kHz

Frequency response 49Hz - 28kHz ±3dB on reference axis

Dispersion Within 2dB of reference response

Horizontal: over 60° arc Vertical: over 10° arc

Sensitivity 88dB spl (2.83V, 1m)

Harmonic distortion 2nd and 3rd harmonics (90dB, 1m)

<1% 100Hz - 100kHz <0.5% 150Hz - 100kHz

Nominal impedance 8Ω (minimum 4.7Ω)

Crossover frequency 4kHz

Recommended amplifier power 50W - 120W into 8Ω on unclipped programme

0.1Ω

Max. recommended

cable impedance

Dimensions Height: 418mm (16.5 in)

Width: 238mm (9.4 in) Depth: 351mm (13.8 in)

Net weight 12kg (26 lb)

Finish Cabinet:







Grilles:

Bowers & Wilkins

www.bowers-wilkins.com

Kevlar is a registered trademark of DuPont. Nautilus is a trademark of B&W Group Ltd. Flowport and Matrix are trademarks of B&W Group Ltd. Copyright © B&W Group Ltd. E&OE B&W Group Ltd reserves the right to amend details of the specification without notice in line with technical developments