

Setting new standards for compact home theatre

Forming the basis of a completely revised Mini Theatre concept, the new M-1 combines a cleaner aesthetic with dramatically improved performance. Combine it with either the ASW608 or the new PV1D subwoofer to create a home theatre experience with superb integration and impressive power for such a discreet system. Plus, its more extended bass response allows M-1 to be used on its own for two-channel applications. Mount the speaker as shown on a table or shelf. Alternatively, a bracket is included for wall mounting and a floor stand is available as an optional extra.



Technical Specifications

Technical features Nautilus™ tube loaded tweeter with aluminium dome

Woven glass fibre cone bass / midrange

Description 2-way vented-box system

Drive units 1x 25mm (1in) aluminium dome high-frequency

1x 100mm (4in) woven glass fibre cone bass / midrange

Frequency range -6dB at 55Hz and 50kHz

64Hz - 23kHz ±3dB on reference axis Frequency response

Dispersion Within 2dB of reference response

Horizontal: over 60° arc Vertical: over 10° arc

Sensitivity 85dB spl (2.83V, 1m)

Harmonic distortion 2nd and 3rd harmonics (90dB, 1m)

<1% 120Hz - 30kHz

Nominal impedance 8Ω (minimum 4.0Ω)

Crossover frequency 4kHz

20W - 100W into 8Ω on unclipped programme Recommended amplifier power

Max. recommended 0.1Ω cable impedance

Height: 248mm (9.8in) **Dimensions**

Width: 114mm (4.5in) Depth: 162mm (6.4in) Mounted on table stand

Net weight 2.3kg (5lb)

Finishes Cabinet: Matte Black or Matte White

Grille: Matte Black or Matte White perforated steel to match