

MORE THAN A FEELING

DALI Low Loss Technology



DALI FAZON SUB 1

DALI FAZON E-9 F

DALI SUB E-12 F

DALI IKON SUB MK2

DALI MENTOR SUB

DALI SUB P-10 DSS

Frequency Range (+/-3 dB) [Hz]	37 - 200	37 - 200	28 - 190	26 - 200	25 - 250	24 - 250
Maximum SPL [dB]	103	111	112	113	111	112
Crossover Frequency [Hz]	50 - 150	40 - 120	40 - 120	50 - 130	40 - 120	40 - 120
Low Frequency Driver	1 x 6.5" long stroke Paper Fibre Cone	1 x 9" long stroke, Aluminium	1 x 12" long stroke, Aluminium	1 x 12" long stroke, Paper Fibre Cone	1 x 10" long stroke Paper Fibre Cone	1 x 10" long stroke Carbon Fibre Cone
Low Frequency Passive Driver	-	-	-	-	-	2 x 10" long stroke Carbon Fibre Cone
Enclosure Type	Closed Box	Bass reflex	Bass Reflex	Bass Reflex	Closed Box	Closed Box with two passive radiators
Bass Reflex Tuning Frequency [Hz]	-	39.0	36.0	29.0	-	31.5
Max. Amplifier Power Output [RMS watt]	150	220	220	325	500	500
Continuous IEC Power Output [RMS watt]	90	170	170	250	300	300
Input Impedance [ohms]	22k	25k	25k	30k	20 k	26k
Connection input(s)	Mono line level (LFE) Stereo line level (low pass filtered) RCA	Mono line level (LFE) Stereo line level (low pass filtered) RCA	Mono line level (LFE) Stereo line level (low pass filtered) RCA	Mono line level (LFE) Stereo line level (low pass filtered) RCA	Mono line level (LFE) Stereo line level (low pass filtered) RCA	Mono line level (LFE) Stereo (low-pass filtered) RCA
Recommended Placement	Floor, near wall or corner	Floor, near wall or corner	Floor, near wall or corner	Floor, near wall or corner	Floor, near wall or corner	Floor, near wall or corner
Recommended Distance From Wall [cm]	5 - 15	> 5	> 5	10 - 100	> 5	> 5
Functions	Crossover Frequency LFE/LP Filter Switch Phase Switch Standby (Auto Power) On/Off Switch Volume (Gain)	Crossover Frequency Phase Switch Standby (Auto Power) On/Off Switch Volume (Gain)	Crossover Frequency Phase Switch Standby (Auto Power) On/Off Switch Volume (Gain)	Crossover Frequency Phase Switch Standby (Auto Power) On/Off Switch Volume (Gain)	Crossover Frequency Remote Control - 3 memories Remote Control - Mute Standby (Auto Power) On/Off Switch Variable Phase Switch Volume (Gain)	Crossover Frequency Remote Control - 3 memories Remote Control - Mute Standby (Auto Power) On/Off Switch Variable Phase Switch Volume (Gain) HIFI/ Cinema Mode
Maximum Power Consumption [W]	195	250	250	500	450	550
Max. Dimensions Incl. Base And Grille (HxWxD) [mm]	255 x 230 x 255	307 x 288 x 311	370 x 340 x 380	476 x 411 x 452	365 x 330 x 340	370 x 340 x 340
Weight [kg]	7.5	11.0	14.7	26.1	22.4	19.5
Accessories Included	Manual Power Cord	Manual, Power cord	Power Cord Manual Rubber Bumpers Spikes M6	Power Cord Manual Rubber Bumpers Spanner For Spikes Spikes M8 White Grille	Battery Type CR2025 Manual Power Cord Remote Control Spikes M10	Manual Power Cord Remote Control Spikes M10 Battery Type CR2025
Optional accessories	-	Grille (Black, White, Ice)	White Grille	White Grille	-	-
Finish	Black High Gloss Lacquer White High Gloss Lacquer	Black Ash Vinyl, Light Walnut Vinyl, White Vinyl	Black Ash Vinyl Light Walnut Vinyl White Vinyl	Black Ash Vinyl Light Walnut Vinyl White High Gloss Vinyl	Black Ash Veneer Cherry Veneer White Satin	Black High Gloss Lacquer White High Gloss Lacquer

All technical specifications are subject to changes without notice. Art. no: 953018-c-2