

Bowers & Wilkins

CM Series



CM6 S2

The top-performing standmounted speaker in the range has a distinctive audiophile feature in common with CM10 S2: the tweeter-on-top design. Combined with a 165mm midrange/bass driver, the result is amazingly lifelike imaging and spaciousness from a speaker of its class.



Technical features	Free-mounted Decoupled Double Dome aluminium tweeter Kevlar® brand fibre cone bass / midrange Flowport™ Tweeter on top
Description	2-way vented-box system
Drive units	1x ø25mm (1 in) Decoupled Double Dome aluminium high-frequency 1x ø165mm (6.5 in) woven Kevlar® cone bass/mid-range
Frequency range	-6dB at 45Hz and 50kHz
Frequency response	50Hz - 28kHz ±3dB
Dispersion	Within 2dB of reference response Horizontal: over 60° arc Vertical: over 10° arc
Sensitivity	88dB spl (2.83V, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 100Hz - 22kHz <0.5% 150Hz - 20kHz
Nominal impedance	8Ω (minimum 3.7Ω)
Crossover frequency	4kHz
Recommended amplifier power	30W - 120W into 8Ω on unclipped programme
Max. recommended cable impedance	0.1Ω
Dimensions	Height: 340mm (13.4 in) cabinet only 403mm (15.9 in) including tweeter Width: 200mm (7.8 in) Depth: 285mm (11.2 in) cabinet only 301mm (11.9 in) including grille and terminals
Net weight	8.9kg (19.6 lb)
Finishes	Cabinet: Grille: Rosnut Black Gloss Black Black Satin White Grey