



# DALI OBERON TECHNICAL SPECIFICATIONS

	OBERON 1	OBERON 3	OBERON 5	OBERON 7	OBERON VOKAL	OBERON ON-WALL
Frequency Range [+/- 3] dB [Hz]	51 - 26,000	47 - 26,000	39 - 26,000	36 - 26,000	47 - 26,000	55 - 26,000
Sensitivity [2.83V/1m] [dB]	86	87	88	88.5	89.5	87
Nominal Impedance [ohms]	6	6	6	6	4	6
Maximum SPL [dB]	106	108	108	110	109	107
Recommended Amp. Power [Watt]	25 - 100	25 - 150	30 - 150	30 - 180	25 - 150	25 - 100
Crossover Frequency [Hz]	2,800	2,400	2,400	2,300	2,600	2,100
Crossover Principle	2-way					
High Frequency Driver	1 x 29 mm soft dome					
Low Frequency Driver(s)	1 x 5¼-inch	1 x 7-inch	2 x 5¼-inch	2 x 7-inch	2 x 5¼-inch	1 x 5¼-inch
Enclosure Type	Bass reflex					
Bass Reflex Tuning Frequency [Hz]	50	49	43	39.5	46	50
Connection Input(s)	Single					
Recommended Placement	Stand/Shelf	Stand/Shelf	Floor	Floor	Shelf	Wall
Recommended distance from rear wall to speaker's rear side [cm]	1 - 50	5 - 50	15 - 80	20 - 80	0 - 50	0 - 10
Dimensions (H x W x D) [mm]	274 x 162 x 234	350 x 200 x 315	830 x 162 x 283	1015 x 200 x 340	441 x 295 x 161	385 x 245 x 120
Dimensions (H x W x D) [inches]	10.8 x 6.4 x 9.2	13.7 x 7.8 x 12.3	32.7 x 6.4 x 11.2	40 x 7.8 x 13.4	17.4 x 11.6 x 6.3	15.2 x 9.7 x 4.7
Weight [kg/lb]	4.2 / 9.2	6.3 / 13.9	10.8 / 23.8	14.8 / 32.5	7.45 / 16.4	4.9 / 10.8
Accessories	Rubber feet, manual	Rubber feet, manual	Spikes, rubber feet, manual	Spikes, rubber feet, manual	Rubber feet, manual	Rubber feet, manual

All technical specifications are subject to change without notice.



IN ADMIRATION OF MUSIC

[www.dali-speakers.com](http://www.dali-speakers.com)

Designed in Denmark