

HD-MD4X1-4KZ-E

4x1 4K60 4:4:4 HDR AV Switcher



- 4K60 4:4:4 digital AV switcher
- HDR10, HDR10+, and Dolby Vision® video formats
- Four HDMI® inputs and one HDMI output
- Automatic switching of inputs
- EDID management
- HDCP 2.3 compliance
- HDMI audio de-embedding
- Device control via CEC
- Enterprise-grade security
- Built-in web interface
- Compatibility with Crestron® 3-Series® or later control systems
- .AV Framework™ technology support
- XiO Cloud® service support
- Compact surface-mountable design
- PoE powered device (optional power pack sold separately)

The HD-MD4X1-4KZ-E is a 4K60 4:4:4 HDR (High Dynamic Range) AV switcher that provides a cost-effective solution for professional AV applications. Equipped with four HDMI® inputs and one HDMI output, the HD-MD4X1-4KZ-E includes features such as automatic switching of inputs, EDID management, HDCP 2.3 compliance, enterprise-grade security, and XiO Cloud® service support.

4K60 4:4:4 and HDR Support

The HD-MD4X1-4KZ-E supports video resolutions up to 4K60 with 4:4:4 color sampling. HDR10, HDR10+, and Dolby Vision® video formats are also supported.

Automatic Switching of Inputs

Automatic switching among the HDMI inputs can occur based on the last connected input or on the routing priority assigned to each input.

Switching behavior is configurable using the web interface or the XiO Cloud® service and is programmable using a Crestron control system. In addition, input selection push buttons on the front panel of the HD-MD4X1-4KZ-E enable the desired inputs to be selected manually.

EDID Management

The HD-MD4X1-4KZ-E provides comprehensive management of EDID (Extended Display Identification Data) to ensure that every source is displayed at the optimal resolution and format. For applications requiring a custom configuration, the HD-MD4X1-4KZ-E enables assessment of the format and resolution capabilities of any device that is connected to the HDMI output of the switcher. The HD-MD4X1-4KZ-E provides the ability to configure signals appropriately for the most desirable and predictable behavior.

HDMI Audio De-embedding

Embedded HDMI 2-channel LPCM audio can be extracted from the selected HDMI input and transmitted to the AUX stereo audio output. Volume and mute control are configurable for the HDMI output and AUX audio output.

Device Control via CEC

Under the management of a control system, CEC (Consumer Electronics Control) over the HDMI connections can control the source and display devices, potentially eliminating the need for dedicated serial cables or IR emitters. CEC over the HDMI output can also enable the display device to be turned on or off automatically without the use of a control system.

Enterprise-Grade Security

The HD-MD4X1-4KZ-E includes advanced security features and protocols. Using 802.1X authentication, Active Directory® credential management, PKI authentication, TLS, SSH, and HTTPS, the HD-MD4X1-4KZ-E provides a true enterprise-grade AV switcher.

Built-In Web Interface

Configuration of the HD-MD4X1-4KZ-E can be accomplished by using the built-in web interface. The configuration of a single unit can be downloaded to a computer or mobile device and then uploaded to multiple HD-MD4X1-4KZ-E units to simplify system installation.

.AV Framework™ Technology Support

In addition to a built-in web interface and control system programming, built-in .AV Framework technology of a Crestron control system can be used to configure and control the HD-MD4X1-4KZ-E. For information about .AV Framework technology and the supported Crestron control systems, visit www.crestron.com/avframework.

HD-MD4X1-4KZ-E

4x1 4K60 4:4:4 HDR AV Switcher

XiO Cloud® Service Support

The HD-MD4X1-4KZ-E is compatible with the XiO Cloud service, which is an IoT (Internet of Things) platform for remotely provisioning, monitoring, and managing Crestron devices across an enterprise or an entire client base. Built on the Microsoft® Azure® software platform and using industry-leading Azure IoT Hub technology, the XiO Cloud service enables installers and IT managers to deploy and manage thousands of devices in the amount of time it previously took to manage a single device. Unlike other virtual machine-based cloud solutions, Azure services provide unlimited scalability to suit the ever-growing needs of an enterprise. For more information, visit www.crestron.com/xiocloud.

Compact Surface-Mountable Design

The HD-MD4X1-4KZ-E can be mounted to a wall or other flat surface. It can also be attached to a single rack rail.

Specifications

Video

Input Signal Types	HDMI with HDR10, HDR10+, Dolby Vision, Deep Color, 4K60 4:4:4 support ^{1,2} (DVI and Dual-Mode DisplayPort™ interface compatible ³)
Output Signal Types	HDMI with HDR10, HDR10+, Dolby Vision, Deep Color, and 4K60 4:4:4 support ^{1,2} (DVI compatible ⁴)
Switcher	4x1 digital AV switcher
Copy Protection	HDCP 2.3
Maximum Resolutions	Common resolutions are listed in the following table.

Scan Type	Resolution	Frame Rate	Color Sampling	Color Depth
Progressive	4096x2160 DCI 4K and 3840x2160 4K UHD	24 Hz	4:4:4	36 bit
		30 Hz	4:4:4	36 bit
		60 Hz	4:2:2	36 bit
		60 Hz	4:4:4	24 bit
	2560x1600 WQXGA	60 Hz	4:4:4	36 bit
	1920x1080 HD 1080p	60 Hz	4:4:4	36 bit
Interlaced (Input Only)	1920x1080 HD 1080i	30 Hz	4:4:4	36 bit

NOTE: Custom resolutions that do not exceed 4096 pixels in width and 2160 pixels in height are supported at pixel clock rates up to 600 MHz.

Audio - General

Digital-to-Analog Conversion	24-bit 48 kHz
Frequency Response	±0.5 dB, 20 Hz to 20 kHz
THD+N	<0.005%, 1 kHz, 10 dBV
S/N Ratio	>95 dB, 10 dBV, 20 Hz to 20 KHz, A-weighted
Crosstalk	≤90 dB, 1 KHz, for multiple inputs only
Stereo Separation	≤80 dB, 20 Hz to 20 kHz

Audio - Source Inputs

Input Signal Type	HDMI (Dual-Mode DisplayPort interface compatible ³)
Formats	Dolby Digital®, Dolby Digital EX, Dolby Digital Plus, Dolby® TrueHD, Dolby Atmos®, DTS®, DTS-ES, DTS 96/24, DTS HD® High Res, DTS-HD Master Audio, DTS:X®, LPCM up to 8 channels

Audio - Digital Output

Output Signal Type	HDMI
Formats	Dolby Digital, Dolby Digital EX, Dolby Digital Plus, Dolby TrueHD, Dolby Atmos, DTS, DTS-ES, DTS 96/24, DTS HD High Res, DTS-HD Master Audio, DTS:X, LPCM up to 8 channels
Source	-80 dB to +20 dB adjustment range, plus Mute
Master Volume	-80 dB to +20 dB adjustment range, plus Mute

Audio - Analog Line Output

Output Signal Type/Format	Stereo 2-channel
Volume Control	-80 dB to +20 dB adjustment range, plus Mute, Mono, and Stereo

Communications

Ethernet	100/1000 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, DHCP, Web browser setup and control, Crestron control system integration, 802.1X, Secure CIP, Authentication, SSH/SSL, TLS
USB	For firmware loading and configuration management and to power a USB powered device
HDMI	HDCP 2.3, EDID, CEC

HD-MD4X1-4KZ-E

4x1 4K60 4:4:4 HDR AV Switcher

Connectors

HDMI IN 1-4	(4) 19-pin Type A connector, female; HDMI digital video/audio inputs (DVI and Dual-Mode DisplayPort interface compatible ³)
HDMI OUT	(1) 19-pin Type A connector, female; HDMI digital video/audio output (DVI compatible ⁴)
AUDIO OUT, AUX	(1) 5-pin 3.5 mm detachable terminal block; Balanced/unbalanced stereo line-level audio output; Output Impedance: <100 Ohms; Maximum Output Level: 4 Vrms balanced, 2 Vrms unbalanced
LAN PoE	(1) 8-pin RJ-45 connector, female; 100BASE-TX/1000BASE-T Ethernet port; PoE (Power over Ethernet) powered device (PD) port; IEEE 802.3at Type 1 (802.3af compatible) Class 0 (12.95 W) compliant, capable of being powered by PoE power sourcing equipment (PSE) ⁵
24 VDC 0.75 A	(1) 2.1 x 5.5 mm DC power connector; 24 VDC power input; PW-2407WU power pack (sold separately)
SERVICE	(1) USB Type A female; For firmware loading and configuration management; Can also provide up to 5 V 500 mA power to USB powered device
G	(1) 6-32 screw, chassis ground lug

Controls and Indicators

PWR	(1) LED. Amber indicates that the device is booting. Green indicates that the device is operational.
AUTO	(1) Push button to enable or disable automatic switching and (1) green LED to indicate that automatic switching is enabled
INPUT 1-4	(4) Push buttons for manual input selection and (4) LEDs. Green indicates that the corresponding input is routed to the output. Amber indicates that a source is detected at the corresponding input but is not routed to the output.
SETUP	(1) Red LED and (1) push button for display of IP address on connected HDMI output

Ethernet

(2) LEDs on RJ-45 LAN connector. Link status LED: Green indicates that a 100BASE-TX link is established. Amber indicates that a 1000BASE-T link is established. Ethernet activity LED: Flashing amber indicates Ethernet activity.

Power

PoE	IEEE 802.3at Type 1 (802.3af compatible) Class 0 (12.95 W) compliant, capable of being powered by PoE power sourcing equipment (PSE) ⁵
Power Pack (Optional)	0.75 A @ 24 VDC; 100-240 VAC, 50/60 Hz; Model: PW-2407WU (sold separately)
Power Consumption	10 W typical

Environmental

Temperature	32° to 104° F (0° to 40° C)
Humidity	10% to 90% RH (noncondensing)
Heat Dissipation	33 BTU/hr typical
Acoustic Noise	Not applicable (fanless)

Construction

Chassis	Metal, black finish, vented sides
Mounting	Surface-mountable or attachment to a single rack rail

Dimensions

Height	8.52 in. (217 mm)
Width	7.0 in. (178 mm)
Depth	1.34 in. (34 mm)

Weight

1.8 lb (0.82 kg)

HD-MD4X1-4KZ-E

4x1 4K60 4:4:4 HDR AV Switcher

Compliance

Regulatory Model M201946001

Bureau Veritas Listed for US & Canada, IC, CE, FCC Part 15 Class B digital device

Model

HD-MD4X1-4KZ-E
4x1 4K60 4:4:4 HDR AV Switcher

Available Accessories

PW-2407WU
Wall Mount Power Pack, 24 VDC, 0.75 A, 2.1 mm, Universal

CEN-SW-POE-5
5-Port PoE Switch

CBL-HD-1.5
Crestron Certified HDMI Interface Cable, 18 Gbps, 1.5 ft (0.45 m)

CBL-HD-3
Crestron Certified HDMI Interface Cable, 18 Gbps, 3 ft (0.91 m)

CBL-HD-6
Crestron Certified HDMI Interface Cable, 18 Gbps, 6 ft (1.8 m)

CBL-HD-12
Crestron Certified HDMI Interface Cable, 18 Gbps, 12 ft (3.6 m)

CBL-HD-20
Crestron Certified HDMI Interface Cable, 18 Gbps, 20 ft (6.1 m)

CBL-HD-30
Crestron Certified HDMI Interface Cable, 10.2 Gbps, 30 ft (9.1 m)

CBL-HD-DVI-1.5
Crestron Certified HDMI to DVI Interface Cable, 1.5 ft (0.45 m)

CBL-HD-DVI-3
Crestron Certified HDMI to DVI Interface Cable, 3 ft (0.91 m)

CBL-HD-DVI-6
Crestron Certified HDMI to DVI Interface Cable, 6 ft (1.8 m)

CBL-HD-DVI-12
Crestron Certified HDMI to DVI Interface Cable, 12 ft (3.6 m)

CBL-HD-DVI-20
Crestron Certified HDMI to DVI Interface Cable, 20 ft (6.1 m)

CBL-HD-DVI-30
Crestron Certified HDMI to DVI Interface Cable, 30 ft (9.1 m)

CBL-HD-LOCK-2
Locking High-Speed HDMI Cable, 10.2 Gbps, 2 ft (0.6 m)

CBL-HD-LOCK-4
Locking High-Speed HDMI Cable, 10.2 Gbps, 4 ft (1.2 m)

CBL-HD-LOCK-8
Locking High-Speed HDMI Cable, 10.2 Gbps, 8 ft (2.4 m)

CBL-HD-LOCK-16
Locking High-Speed HDMI Cable, 10.2 Gbps, 16 ft (4.8 m)

MPI-WP150-120
Media Presentation Wall Plate – International Version – HDMI with Mini-TRS Stereo Audio, White

MPI-WP150-122
Media Presentation Wall Plate – International Version – HDMI with Mini-TRS Stereo Audio, Anthracite

MP-WP152-A
Media Presentation Wall Plate – HDMI, Almond

MP-WP152-B
Media Presentation Wall Plate – HDMI, Black

MP-WP152-W
Media Presentation Wall Plate – HDMI, White

Notes:

- 3D formats are not supported.
- 4K60 4:4:4 performance and HDR support require the use of HDMI cables and couplers with a minimum TMDS bandwidth of 18 Gbps. If 4K60 4:2:0 or 4K30 4:4:4 performance is acceptable, cables and couplers with a minimum bandwidth of 10.2 Gbps may be used. Bandwidth loss is cumulative; therefore, performance may be reduced when inserting multiple cables and couplers inline.
- The HDMI input requires an appropriate adapter or interface cable to accommodate a DVI or Dual-Mode DisplayPort signal. CBL-HDI-DVI interface cables are available separately.
- The HDMI output requires an appropriate adapter or interface cable to accommodate a DVI signal. CBL-HDI-DVI interface cables are available separately.
- In order for the LAN PoE port to receive PoE, the port must be connected to a PoE compliant Ethernet switch or to other equipment that has a PoE power sourcing equipment (PSE) port. Cabling that connects to a PoE PSE port is designed for intrabuilding use only.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to www.crestron.com/warranty for full details.

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

HD-MD4X1-4KZ-E

4x1 4K60 4:4:4 HDR AV Switcher

Crestron, the Crestron logo, .AV Framework, 3-Series, and XiO Cloud are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby, Dolby Atmos, Dolby Digital, and Dolby Vision are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS, DTS HD, and DTS:X are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. HDMI and the HDMI logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Microsoft, Active Directory, and Azure are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. DisplayPort is either a trademark or registered trademark of Video Electronics Standards Association in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2020 Crestron Electronics, Inc.

Rev 08/28/20

HD-MD4X1-4KZ-E

4x1 4K60 4:4:4 HDR AV Switcher

