

**NEW!
2024**

DALI RUBIKORE 6

Powerful with an enhanced and controlled performance

The DALI RUBIKORE 6 floorstanding loudspeaker features twin 6½-inch SMC and Clarity Cone™ Technology paper and wood fibre woofers, integrated with the unique DALI Hybrid Tweeter. The twin woofers combine at low frequencies to create room filling bass bandwidth and volume. At midrange frequencies, just one woofer takes over to focus on the core of the music, to which the Hybrid Tweeter adds immense musical detail and clarity.

EVOLUTION THROUGH KORE TECHNOLOGY

Inspired by the DALI KORE, the RUBIKORE 6 employs Clarity Cone™ Technology, SMC drivers, SMC-KORE™ inductors, a Hybrid Tweeter module with a brand new Low-Loss dome tweeter without ferrofluid and Continuous Flare bass reflex ports to maximise its performance and high-end sound quality.

EXCEPTIONAL ACOUSTIC PERFORMANCE

The fast and incisive DALI KORE inspired RUBIKORE 6 is designed for ambitious high-end stereo and home theatre systems in medium to larger sized rooms where its compact floor-stand design provides great installation versatility. The RUBIKORE 6 combines two 6½ inch paper and wood fibre Clarity Cone™ Technology SMC bass/midrange drivers with a DALI Hybrid dome and planar tweeter to create extraordinary low loss, amplifier optimised, wide dispersion sound quality.

DANISH FURNITURE DESIGN AND HIGH-END FINISHES

The long tradition of Danish joinery and cabinet making craft is fully expressed in the RUBIKORE 6. Thanks to its slim floor-stand design the RUBIKORE 6 is compact and stylish with exquisite craftsmanship and finishing. In addition to aesthetic beauty, the internally braced RUBIKORE 6 cabinet also provides the immensely rigid and inert platform that high performance electro-acoustics demands.

HAND-CRAFTED BY DALI

The RUBIKORE 6 is hand-crafted and assembled at DALI in Denmark and is predominantly a product of in-house skill, expertise, design, and manufacture. But in addition to its Danish assembly, the RUBIKORE 6 also calls on numerous nearby component suppliers and skills to reinforce its fully Danish roots. The RUBIKORE 6 is Danish to the core.



DALI


IN ADMIRATION OF MUSIC

TECHNICAL SPECIFICATIONS



See the full DALI PHANTOM range on dali-speakers.com

DALI RUBIKORE	RUBIKORE 6
Frequency range	38 - 34,000 Hz ±3 dB
Sensitivity	88.5 dB @ 1 m for 2.83 V
Nominal impedance	4 ohm
Maximum SPL	110dB
Crossover frequency	800 / 2,600 / 14,000 Hz
Crossover principle	2½ + ½-way
Recommended amplifier power	40 - 200 Watt
High frequency driver(s)	17 x 45 mm planar magnetostatic tweeter 1 x 29 mm low loss soft dome
High frequency diaphragm	Planar magnetostatic Soft woven fabric
Low/Mid frequency driver(s)	2 x 6½ inch
Low/mid frequency diaphragm	Clarity Cone™ paper and wood fibre
Connection input(s)	Bi-wire / Bi-amp
Enclosure type	Bass reflex
Bass reflex tuning frequency	34 Hz
Other features	N/A
Recommended placement	Floor
Recommended distance from rear wall	20 - 180 cm
Dimensions (H x W x D)	990 x 200 x 380 mm 39.1 x 7.9 x 15.0 inches
Weight incl. grille	23 kg 50.7 lb
Shipping weight	25 kg 55.1 lb
Finishes	High Gloss Black High Gloss Maroon Natural Walnut High Gloss White
Accessories	Manual Polishing cloth (high gloss finish only) Front grille Premium spike set
Spike thread size	M8




High Gloss Black




High Gloss White



Natural Walnut



High Gloss Maroon



Scan QR code for more information